

FB-5060

FIRE-RATED UNINSULATED

Application

- For wall applications
- Designed to maintain continuity in a 2 hour fire rated wall, when temperature is not a factor

Product Features

- Concealed hinge • Self-closing • Self-Latching
- Inside latch release
- Available with a removable door panel

FB-5060 Access Door Specifications:

Door / Door Frame: Steel or Stainless Steel: 16 gauge door, 16 gauge mounting frame. Flush to frame with reinforced edges, flange to be 1" wide.

Hinge: Concealed.

Fire Rating (Walls): UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label. (optional)
Max sizes 36 x 48 and 24" x 79".

Standard Compliances: UL 10B; CAN/ULC S104; NFPA 80.

Standard Latch: Universal self-latching bolt, operated by either a knurled knob or flush key.
When master keying is required, doors can be prepared for rim or mortise cylinder locks.

Finish: Baked White Prime Coat.

(Additional finish paint is recommended for superior corrosion resistance).

FB-5060 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door		
Inches	mm		lbs.	kg.
8 X 8	203 X 203	1	5.5	2.5
10 X 10	254 X 254	1	6.5	2.9
12 X 12	305 X 305	1	8.2	3.7
14 X 14	356 X 356	1	8.3	3.8
16 X 16	406 X 406	1	11.1	5.0
18 X 18	457 X 457	1	13.8	6.3
20 X 20	508 X 508	2	18.0	8.2
22 X 22	559 X 559	2	21.0	11.3
22 X 30	559 X 762	2	24.9	12.5
22 X 36	559 X 914	2	27.5	12.5
24 X 24	610 X 610	1	20.1	9.1
24 X 30	610 X 762	2	25.6	11.6
24 X 36	610 X 914	2	29.7	13.5
24 X 48	610 X 1219	2	35.7	16.2
30 X 30	762 X 762	2	28.4	12.9
36 X 36	914 X 914	2	38.7	17.6
36 X 48	914 X 1220	2	48.8	22.1

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

