

SD-6000

SECURITY DOORS Heavy Security Access Door

Application

- Installation ideal for prisons, correctional facilities, housing projects etc.
- Heavy duty access door designed for use in high security areas

Product Features

- 10 Gauge Door
- Security butt hinges are surface welded to the door and frame
- A detention type deadbolt lock with paracentric key is standard

SD-6000 Access Door Specifications:

Door / Door Frame: Door 10 gauge (.134) plate & frame is 2x2x3/16 angle, flush to edge of frame. Mounting frame to have anchor straps.

Hinge: Heavy duty butt hinges, welded to door and frame.

Standard Latch: Detention type deadbolt lock with paracentric key.

Optional Latches/Locks: Tamperproof security cam latches, cylinder lock and key. When master keying is required, doors can be prepared for rim or mortise cylinder locks.

Finish: Baked White Prime Coat.

(Additional finish paint is recommended for superior corrosion resistance)




SD-6000 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
Inches	mm	lbs.	kg.
12 X 12	305 X 305	23	10.3
16 X 16	406 X 406	30	13.7
18 X 18	457 X 457	34	15.6
24 X 24	610 X 610	49	22.3
24 X 36	610 X 914	65	29.5
36 X 36	914 X 914	87	39.4

Wall or ceiling opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet



Detention Lock with Paracentric Key

