

WD-8000

DUCT & SPECIALTY DOOR Walk Through Door

Application

- Designed to provide convenient walk through access to duct work interiors & air handling units
- Low to medium pressure systems and plenums

Product Features

- Heavy duty construction, along with a continuous hinge and compression handles
- Optional Features: Removable Door Panel / Vision Panel / High Pressure Units / Key Operated Handles

WD-8000 Door Specifications:

Material: Galvanized steel, also available in Aluminum and Stainless Steel

Door: 22 gauge

Mounting Frame: Double panel frame is 1 15/16" wide x 1 1/2" deep extruded aluminum with mitred corners

Gasket: 1/8" thick x 1/2" wide closed cell neoprene gasketing between door and frame

Hinge: Continuous steel piano hinge-opens 180 degrees

Insulation: Door panel filled with 1" thick fiberglass insulation - 4 R value

Standard Latch: Dual acting compression handles-operable from both sides,
Units 48" high and under to have 2 handles,
Units over 48" high to have 3 handles.

Finish: Mill finish



WD-8000 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
24 X 36	610 X 914		21.0	9.5
24 X 48	610 X 1219		28.2	12.8
24 X 60	610 X 1524		33.8	15.3
24 X 72	610 X 1829		41.7	18.9
30 X 36	762 X 914		25.3	11.5
30 X 48	762 X 1219		36.2	16.4
30 X 60	762 X 1524		42.5	19.3
30 X 72	762 X 1829		80.6	36.6

Wall or ceiling opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

